

Specifications

Load Capacity	2200 lbs.
Fork Length	45"
Overall Fork Widths	20.5" / 27"
Lowered Fork Height	3.3"
Raised Fork Height	31.5"
Fork Width	6.3"
Weight	375 lbs.
Casters	7" x 2"
Load Rollers	3" x 2"
Load Center	22.5"
Overall Length	60"
Turning Radius	53.5"



The **CJ22XM Manual Hi-Rise Scissor Lift** is designed to handle applications such as lifting and transporting skids and bottomless containers, loading and unloading conveyor systems, and is also perfectly suited as a mobile work station.

Built to work like a Stacker and a Pallet Truck combined, the ergonomic design of the **CJ22XM** enables the operator to place the load at the required work height thereby eliminating bending and back injuries which results in reduced costly workman compensation claims.

Standard Features

Frame

- Rugged Heavy Duty Frame constructed of one-piece formed channel steel offering light weight strength.

Forks

- Reinforced for added strength with tapered ends for easy pallet entry.

Paint

- The CJ22XM boasts a quality Powder Coat finish.

Hydraulic Pump

- Quality design complete with a special lowering valve allowing controlled rate of descent, and an overload bypass valve.
- The triple stage piston rod design provides rigidity and light pumping force.
- The pump is designed with a Quick-Lift function that doubles the lifting speed when lifting loads less than 500 lbs.

Pump Stroke

- Features a full 90 degree top to bottom stroke requires only 18 strokes to raise the forks to the maximum lift.

Handle

- Featuring a reinforced base, the spring-a-matic handle returns to the upright position automatically.

Control Handle

- The control handle has three positions (raise/neutral/lower) fingertip control. Ergonomically designed and free of pinch points.

Steering

- Featuring 150 degree pivot action for greater maneuverability with 7" polyurethane swivel casters providing maximum rolling ease and maneuverability in tight areas.

Load Rollers

- The durable 3" polyurethane rollers are situated in the scissor legs for easy mobility.

Brakes

- The self adjusting stabilizers are automatically applied when lifting loads higher than 15.75" which ensures that the load will remain stable particularly when using the truck as a work positioner.

Scissor Legs

- The extra long steel scissor legs provide extra stability particularly when handling unevenly loaded skids.