

Specifications

Load Capacity	4500 lbs.
Fork Length	45"
Overall Fork Widths	21.5"/27.75"
Lowered Fork Height	3"
Raised Fork Height	7.75"
Fork Width	6.5"
Weight	170 lbs.
Steer Wheels	6.25" x 2"
Load Rollers	2.75" x 3.6"
Wheels/Rollers	Polyurethane

Description

The **CJ44W & CJ44WA Manual Weigh Scale Pallet Jacks** enable the operator to easily lift, weigh (to **99.9% accuracy**) and transport loads. The easy to read meter features a large LCD display for better visibility, keypad and automatic tare functions. The readout is available in pounds or kilograms. Can be used with internal rechargeable battery source or external AC input.

Standard Features

Frame

- Rugged Heavy Duty Frame constructed of one-piece formed channel steel offering light weight strength.

Forks

- Reinforced for added strength with tapered ends for easy pallet entry.

Paint

- The CJ44W boasts a quality Powder Coat finish.

Hydraulic Pump

- Quality design complete with a special lowering valve allowing controlled rate of descent, and an overload bypass valve.

Handle

- Featuring a reinforced base, the spring-a-matic handle returns to the upright position automatically.

Control Handle

- The control handle has three positions (raise/neutral/lower) fingertip control. Ergonomically designed and free of pinch points.

Load Rollers

- Features 2.75" polyurethane rollers with sealed bearings.



Rechargeable Battery Pack

- Rechargeable battery pack built into the LCD readout panel. Readout panel has a standard 110 V plug in capability (the plug in cord comes standard with the unit as well) so they can use either battery or AC power. Also standard is a built in charger that charges the battery pack whenever the unit is plugged in.

Pump Stroke

- Features a full 90 degree top to bottom stroke requires only 10 strokes to raise the forks to the maximum lift.

Steering

- Featuring 200 degree pivot action for greater maneuverability with 6.3" polyurethane wheels, sealed bearings and "Ball-Thrust" steering.

Push Rods

- The adjustable push rods allow for individual adjustment capability of either fork height.

Hangers

- The one piece hangers are constructed of Iron Cast for greater strength and longevity.

Helper Rollers

- Features 4 helper rollers for easy exit and entry of pallets.

Pivot Points

- The CJ44W features grease fittings and bushings at all pivot points for easy maintenance.

Options

- CJ44WA adds an Automotive Brake Attachment to the CJ44W.

Официальный дилер: ООО «Форклифт», тел./факс: (499) 951-79-99 (многоканальный)

Екатеринбург: (343) 344-00-22, Пермь: (342) 294-40-49, Челябинск: (351) 211-54-25, Тюмень: (345) 238-28-26

E-mail: sales@forklift.ru, Web: www.forklift.ru, Skype: forklift-ural