

STANDARD PALLET JACK

CJ55
CJ55C
CJ55T
CJ55A

Specifications

	CJ55/T/A	CJ55C
Load Capacity	5500 lbs.	5500 lbs.
Fork Length	48"	23"
Overall Fork Widths	20.5"/ 27"	16"
Lowered Fork Height	2.9"	2.9"
Raised Fork Height	7.8"	7.8"
Fork Width	6.5"	6.5"
Weight	170 lbs.	165 lbs.
Steer Wheels	7"	7"
Load Rollers	2.9" x 3.6"	2.9" x 3.6"
Wheels/Rollers	Polyurethane	Polyurethane

Description

Durable, versatile and easy to use the **CJ55** features an ergonomic design that reduces operator fatigue and downtime. A 200 degree handle pivot provides exceptional maneuverability in compact areas and comes with standard polyurethane wheels and rollers for rolling ease. The **CJ55T** has tandem load rollers and the **CJ55A** comes with the Automotive Brake Attachment. The **CJ55C** includes all of the same features as the CJ55 and is made to operate in extremely compact areas.

Standard Features

Frame

- Rugged Heavy Duty Frame constructed of one-piece formed channel steel offering light weight strength.

Forks

- Reinforced for added strength with tapered ends for easy pallet entry.

Paint

- The CJ55 series boasts a quality Powder Coat finish.

Hydraulic Pump

- Quality design complete with a special lowering valve allowing controlled rate of descent, and an overload bypass valve.

Handle

- Featuring a reinforced base, the spring-a-matic handle returns to the upright position automatically.

Control Handle

- The control handle has three positions (raise/neutral/lower) fingertip control. Ergonomically designed and free of pinch points.

Pump Stroke

- Features a full 90 degree top to bottom stroke requires only 10 strokes to raise the forks to the maximum lift.

Load Rollers

- Features 2.9" polyurethane rollers with sealed bearings.

Steering

- Featuring 200 degree pivot action for greater maneuverability with 7" polyurethane wheels, sealed bearings and "Ball-Thrust" steering.

Push Rods

- The adjustable push rods allow for individual adjustment capability of either fork height.

Hangers

- The one piece hangers are constructed of Iron Cast for greater strength and longevity.

Helper Rollers

- Features 4 helper rollers for easy exit and entry of pallets.

Pivot Points

- The CJ55 features grease fittings and bushings at all pivot points for easy maintenance.

Options

- Automotive Brake Attachment - CJ55A
- Tandem Wheels - CJ55T
- Nylon Wheels
- Steel Wheels



Официальный дилер: ООО «Форклифт», тел./факс: (499) 951-79-99 (многоканальный)

Екатеринбург: (343) 344-00-22, Пермь: (342) 294-40-49, Челябинск: (351) 211-54-25, Тюмень: (345) 238-28-26

E-mail: sales@forklift.ru, Web: www.forklift.ru, Skype: forklift-ural