Specifications

	4
Load Capacity	5500 lbs.
Fork Length	48"
Overall Fork Widths	20.5"/ 27"
Lowered Fork Height	2.9"
Raised Fork Height	7.8"
Fork Width	6.5"
Weight	170 lbs.
Steer Wheels	7"
Load Rollers	2.9" x 3.6"
Wheels/Rollers	Nylon

Description

Whether it is a Clean-Room or Cold-Room environment, or a highly corrosive chemical application, the **CJ55G Galvanized Pallet Jack** will do the job. Ideal for use in freezers or coolers with temperatures down to -10 degrees F, as well as chemical exposure applications, the **CJ55G** is hygienic, durable, easy to clean and built for the ultimate in Corrosion Resistance.

Standard Features

Galvanized Frame

 Rugged Heavy Duty Frame constructed of one-piece formed channel steel offering light weight strength.

Galvanized Forks

 Reinforced for added strength with tapered ends for easy pallet entry.

Galvanized Hydraulic Pump

 Quality design complete with a special lowering valve allowing controlled rate of descent, and an overload bypass valve.

Galvanized Handle

• Featuring a reinforced base, the spring-a-matic handle returns to the upright position automatically.

Control Handle

 The control handle has three positions (raise/neutral/ lower) fingertip control. Ergonomically designed and free of pinch points.

Pump Stroke

 Features a full 90 degree top to bottom stroke requires only 10 strokes to raise the forks to the maximum lift.

Steering

• Featuring 200 degree pivot action for greater maneuverability with 7" nylon wheels, sealed bearings and "Ball-Thrust" steering.

Load Rollers

• Features 2.9" nylon rollers with sealed bearings.

Galvanized Push Rods

• The adjustable push rods allow for individual adjustment capability of either fork height.

Galvanized Hangers

 The one piece hangers are constructed of Iron Cast for greater strength and longevity.

Helper Rollers

• Features 4 helper rollers for easy exit and entry of pallets.

Pivot Points

 The CJ55G features grease fittings and bushings at all pivot points for easy maintenance.

Options

- Automotive Brake Attachment
- · Tandem Wheels

Официальный дилер: ООО «Форклифт», тел./факс: (499) 951-79-99 (многоканальный)

Екатеринбург: (343) 344-00-22, Пермь: (342) 294-40-49, Челябинск: (351) 211-54-25, Тюмень: (345) 238-28-26

E-mail: sales@forklift.ru, Web: www.forklift.ru, Skype: forklift-ural